



MAINTENANCE OIL

Ideal for refreshing and maintaining Polyx®-Oil surfaces.



3079 Clear
Matt



3081 Clear
Satin



3098 Clear
Semi-matt
Anti-Slip (R9)



3440 White
Transparent



1 COAT

PRODUCT DESCRIPTION

Clear or transparent, fast drying wood finish for the basic care and maintenance of oiled/waxed wooden floors. Dull and matt flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil at the right time, time-consuming sanding works and renovation can be avoided. Also suitable for changing the gloss level of intact surfaces treated with Osmo Polyx®-Oil.

Suitable for wood; microporous surface does not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water according to DIN 68861-1A – no water spots. When dry, finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and is saliva-resistant and sweatproof according to DIN 53160 (German industrial norm).

RECOMMENDED USE

Osmo Maintenance Oil is ideal for maintaining all wooden flooring treated with Polyx®-Oil, such as solid wood and plankwood flooring, parquet, blockstrip, OSB and cork flooring, as well as stairs and furniture. Highly recommended for public spaces (e.g. restaurants, museums and other high traffic floors).

INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Deodorized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope.

Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.85-0.95 g/cm³

Viscosity: 40-60s DIN 53211/3 mm

Odour: faint/mild, after drying odourless

Flash point: >60°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

SURFACE PREPARATION

Wood surface must be clean, dry (moisture content max. 18 %) and free of dust.

Osmo Maintenance Oil is ready to use, please do not thin. Shake well before use.

Clean the surface thoroughly with Osmo Intensive Cleaner and rinse (damp mopping) with clear water.

The finished surface is, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION

Apply thinly and evenly to the clean and dry wood along the wood grain with Osmo Double Blade Scraper or Osmo Microfibre Roller, and massage into the wood with a white pad (do not massage in 3098). Remove excess product.

For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth.

Allow for good ventilation while drying.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).



DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

COVERAGE

1 litre covers approx. 40-60 m² with one coat.
Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

NOTE

The maintenance results are, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces. When applying to raw or already greyed wood, the surface must be sanded and treated with Osmo Polyx®-Oil. Do not massage in Maintenance Oil 3098 Semi-Matt/Anti-Slip with a single disc machine.

CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Contains 2-butanonoxime. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations.

Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

3079 Clear Matt
3081 Clear Satin
3098 Clear Semi-Matt/Anti-Slip (R9)
3440 White Transparent

CAN SIZES

1 L; 2.50 L; 10 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15